

# Displays & Monitors

OPX Series: 15", 15.6", 17", 18.5", 19", 21.5", 23.6", 27", 32"

## Features

- 15" to 32" Full HD Display Size Options
- Full Flat, IP65 Waterproof Front Panel
- Capacitive Touch Screen
- USB,VGA and HDMI



## Quality Standards

- Complies with CE, RoHS



SKU	Size	Color	Material	Touch Screen	IPRating	Package
X-15"	15"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-15.6"	15.6"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-17"	17"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-18.5"	18.5"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-19"	19"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-21.5"	21.5"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-23.6"	23.6"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-27"	27"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual
X-32"	32"	Silver	Die-casting Aluminum	Capacitive	IP65Rated Front Bezel	Individual

SKU	X-15"	X-15.6"	X-17"	X-18.5"	X-19"
Screen Size	15"	15.6"	17"	18.5"	19"
Resolution	1024*768	1366*768	1280*1024	1920*1080	1280*1024
Viewing Angle	89/89/89/89	45/45/20/40	85/85/80/80	89/89/89/89	85/85/80/80
Brightness	350 cd/m²	200 cd/m²	250 cd/m²	250 cd/m²	250 cd/m²
Contrast Ratio	1000:1	500:1	1000:1	1000:1	1000:1
Touch Screen	Capacitive				
Controller	USBinterface				
Durability	≥500W times				
USB	1 *USB(For touchscreen cable)				
Display	1 *HDMI, 1 *VGA				
Dimensions (mm)	358.4*286.7*49.5	392.04*242*49.5	384.1*316.2*50.7	457.3*281.7*49.6	429*356.5*49.2
Hole Sizes (mm)	349.4*277.2	387.2*237.2	381*312.9	453.4*277.5	425.5*350.5
ndividual Gross Weight (KG)	3.70	3.70	5.60	4.10	6.20
Mounting Options	Embedded / Wall-mounted / Desktop				
Operating Temperature	-10 ~+60°C	-10 ~+60°C	-10 ~+60°C	-10 ~+60°C	-10 ~+60°C
Storage Temperature	-20 ~+70°C	-20 ~+60°C	-20 ~+60°C	-20 ~+60°C	-20 ~+60°C
Storage Humidity *Non-condensing	5 ~95%	5 ~95%	5 ~95%	5 ~95%	5 ~95%
Power Input	DC 12V (3A)				
Packaging Information	1 *Master, 1 *Adapter, 1*Power Supply Cable, 1 *Touch Screen Cable, 1 *VGA cable, 1 *Manual, 1 *Warranty Card				

SKU	X-21.5"	X-23.6"	X-27"	X-32"
Screen Size	21.5"	23.6"	27"	32"
Resolution	1920*1080	1920*1080	1920*1080	1920*1080
Viewing Angle	89/89/89/89	89/89/89/89	89/89/89/89	89/89/89/89
Brightness	250 cd/m²	250 cd/m²	250 cd/m²	250 cd/m²
Contrast Ratio	3000:1	3000:1	1000:1	1200:1
Touch Screen	Capacitive			
Controller	USBinterface			
Durability	≥500W times			
USB	1 *USB(For touchscreen cable)			
Display	1 *HDMI, 1 *VGA			
Dimensions (mm)	533.6*320.9*51.3	572.1*345.6*51.3	657*398*51.5	770.7*465.6*57.2
Hole Sizes (mm)	527.9*314.9	567.6*341.2	651.1*394.2	765.6*460.3
ndividual Gross Weight (KG)	5.70	6.00	9.20	12.50
Mounting Options	Embedded / Wall-mounted / Desktop			
Operating Temperature	-10 ~+60°C	-10 ~+60°C	-10 ~+60°C	-10 ~+60°C
Storage Temperature	-20 ~+60°C	-20 ~+60°C	-20 ~+60°C	-20 ~+60°C
Storage Humidity *Non-condensing	5 ~95%	5 ~95%	5 ~95%	5 ~95%
Power Input	DC 12V (3A)			
Packaging Information	1 *Master, 1 *Adapter, 1*Power Supply Cable, 1 *TouchScreen Cable, 1 *VGA cable, 1 *Manual, 1 *WarrantyCard			